USB Connector Over Temperature IC

General Description

WAYON

WP1682 is a temperature protection IC for USB or Type-C charging connector, with external NTC Thermistor, controlling built-in NMOS switch through inner delay and logic processing circuits to protect charging equipment.

WP1682 is an overheating protection product, using charge pump driver to control the switching state of built-in power NMOS switch on VBUS. When the external NTC resistance sensing temperature is within the normal range, the power NMOS is on. While the NTC sensing temperature is too high and is confirmed to exceed the set value by the internal logic and delay processing, the power NMOS will be shut off to pull down VBUS power supply to protect charging equipment, until the NTC cools down again, after reset by re-plugging the power supply or equipment, NMOS switch would be turned on to restore VBUS power supply.

Applications

• USB or Type-C connector for charger

Features

- TH pin detection voltage: (VDD=5V) 4.165V (0.833×VDD) ±0.055V
- TH pin detection dead time: > 20ms
- Low voltage Detect Delay time: > 20ms
- Reset release Delay time: < 200ms
- On-resistance of NMOS switch: $5m \Omega$ (Typ)
- Reset release Voltage: < 4.5V
- Working temperature range: -40 ~ 85 °C
- Package: DFN-8 (0303*0.75-0.65)



Note: This is a typical appication of chip for reference only.



Pin Configuration



(TOP VIEW)

Pin Description

| Pin Number | Pin Name | I/O | Function |
|------------|----------|--------|---|
| 1 | GND | Input | Ground |
| 2 | ТН | Input | Temperature detection input. |
| 3 | NC | 1 | / |
| 4 | сс | Input | Device end plugging detection input, recommended to connect to type-C interface CC pin or to pull up to VDD by Rp. Connect to GND to bypass device end plugging detection. |
| 5,6,7,8 | VBUS | Output | Output Voltage. Output of internal NMOS switch and power supply for load. |
| ТАВ | VDD | Input | Power supply |

WAYON

Absolute Maximum Ratings

| Items | Symbol | Ratings | Unit |
|----------------------|--------|--------------|------|
| Supply voltage | VDD | -0.3~16 | V |
| OUT terminal voltage | VOUT | -0.3~VDD+0.3 | V |
| Storage temperature | Tstg | -55~125 | °C |
| Operating ambient | Topr | -40~85 | °C |
| Operating voltage | Vop | 3.3~13.5 | V |
| Power dissipation | Pd | 1000 | mW |

Note: Stresses at or above those listed under Absolute Maximum Ratings may cause permanent damage to the product. This is a stress rating only; functional operation of the product at these or any other conditions above those indicated in the operational section of this specification is not implied. Operation beyond the maximum operating conditions for extended periods may affect product reliability.



Electrical Characteristics

(T_A=25 °C, V_IN=5V, unless otherwise noted)

| Parameter | Symbol | Test Condition | MIN | ТҮР | MAX | Unit |
|---|----------|---|-----------|-----------|-----------|------|
| Recommended Operating Voltage | VDD | | 3.3 | | 13.5 | V |
| Consumption current 1 | ldd1 | VDD=5V | | 40 | | uA |
| Consumption current 1 | ldd2 | VDD=12V | | 80 | | uA |
| TH pin detection voltage 1 | Vth1 | VDD=5V TH=2.5V->Vth1 | 4.110 | 4.165 | 4.220 | V |
| TH pin detection voltage 2 | Vth2 | VDD=5V,9V,12V TH=0.5×VDD ->Vth2 | 0.822×VDD | 0.833×VDD | 0.844×VDD | V |
| TH pin detection dead time | tvth | VDD=5V | 20 | | 150 | ms |
| Low voltage Detect | Vdet | VDD=5V->Vdet TH=0.5×VDD | Vrel-0.4 | | Vrel-0.1 | V |
| Low voltage Detect Delay time | tvdet | VDD=5V->3.5V TH=0.5×VDD | 20 | | 150 | ms |
| Reset detection voltage | Vrst | VDD=5V->Vrst TH=0.5×VDD | Vdet-0.4 | | Vdet-0.1 | V |
| Reset release voltage | Vrel | VDD=0V->Vrel TH=0.5×VDD | 3 | | 4.5 | V |
| Reset release Delay time | tvrel | VDD=Vrst->5V TH=0.5×VDD | 30 | | 200 | ms |
| TH pin open detection voltage | Vth_open | VDD=5V,9V,12V TH=0.5×VDD ->Vth_open | TYP-70mV | 0.03×VDD | TYP+70mV | V |
| Thermistor open detection Delay time | Topen | VDD=5V TH=0.5×VDD->0V | 20 | | 150 | ms |
| Threshold voltage of CC | Vcc | VDD=5V,9V,12V | 0.42×VDD | 0.44×VDD | 0.46×VDD | V |
| On-resistance of NMOS switch | Ron | VDD=5V,Iload=1A | | 5 | | mΩ |



Flow diagram



Block Diagram





Temperature detection timing chart



< Abnormal temperature detection >

When TH voltage exceeds Vth1 or Vth2 and keeps Tvth, the chip determines that the temperature exceeds the set threshold. The internal NMOS switch would be shut off to pull down VBUS power supply to protect charging equipment. After the over-temperature protection is started, if the temperature drops below the threshold again, that is, when the TH voltage is lower than Vth1 or Vth2, NMOS will not be turned on. After resetting the chip (VDD is lower than Vrst or Vcc>0.44× VDD), the chip can enter normal mode.

TH voltage is greater than the threshold voltage Vth (0.833*VDD) and TH voltage is less than Vth_open, and the chip's response is consistent



Low voltage detection timing chart



Low voltage detection timing chart

When VDD voltage is lower than Vdet but not lower than Vrst and tvdet is maintained, the chip will determine that the work is low voltage. The internal NMOS switch would be shut off to pull down VBUS power supply to protect charging equipment. After the low voltage protection is started, NMOS will not open if the VDD voltage is higher than Vdet again. After resetting the chip (VDD is lower than Vrst or Vcc>0.44×VDD), the chip can enter normal mode.

Device end plugging detection identification

When the voltage of CC is higher than 0.44×VDD, the chip immediately enters the reset state. The internal NMOS switch would be shut off to pull down VBUS power supply. Connect CC to GND to bypass device end plugging detection.

When this feature is not used, CC should be connected to GND.



Temperature threshold setting



NTC thermistor : NCP21XV103J03RA (Murata Manufacturing Co., Ltd.) R=10K ±1% Reference value: B constant number (25°C-80°C)=3930 t1(Detection temperature)=75°C, t0(Reference temperature)=25°C





Temperature setting formula

temperature threshold:

$$=\frac{1}{\frac{\ln(\text{Rf}*(1-0.833)/(0.833*\text{R}))}{\text{B}}+(1/(273.15+25))}}$$

in here:

Rf is the feedback resistance value in series with NTC resistance, R is the resistance value of thermistor at 25 degrees Celsius, and B is a constant of NTC resistance.

According to the above formula, the set temperature threshold can be calculated according to the feedback resistance value (Rf), or the required feedback resistance can be calculated according to the set temperature threshold.

Device end plugging detection



When the type-C interface is unplugged, CC voltage is pulled up to VDD by Rp, the chip would be reset. The internal NMOS switch would be shut off to pull down VBUS power supply to protect charging equipment. When the type-C interface is plugged in, CC voltage is pulled down by Rd below 0.44×VDD, the chip would enter normal mode after Tvrel.



Package Information



| eva mor | MILLIMETER | | | |
|------------------|------------|------|------|--|
| STMBOL | MIN | NOM | MAX | |
| А | 0.70 | 0.75 | 0.80 | |
| A1 | | 0.02 | 0.05 | |
| b | 0.25 | 0.30 | 0.35 | |
| с | 0.18 | 0.20 | 0.25 | |
| D | 2.90 | 3.00 | 3.10 | |
| D2 | 2.40 | 2.50 | 2.60 | |
| e | 0.65BSC | | | |
| Nd | 1.95BSC | | | |
| E | 2.90 | 3.00 | 3.10 | |
| E2 | 1.45 | 1.55 | 1.65 | |
| L | 0.30 | 0.40 | 0.50 | |
| h | 0.20 | 0.25 | 0.30 | |
| L/F载体尺寸 (nil) | 106*75 | | | |

Ordering Information

| Part Number | Package | Packing Quantity | Marking |
|-------------|--------------|------------------|-------------|
| WP1682 | DFN8-3mm*3mm | 3k/Reel | WP1682 XXXX |

Contact Information

No.1001, Shiwan(7) Road, Pudong District, Shanghai, P.R.China.201202

Tel: 86-21-68960674 Fax: 86-21-50757680 Email: market@way-on.com

WAYON website: http://www.way-on.com

For additional information, please contact your local Sales Representative.

DITUN is registered trademark of Wavon Corporation.

Specifications are subject to change without notice.

The device characteristics and parameters in this data sheet can and do vary in different applications and actual device performance may vary over time Users should verify actual device performance in their specific applications.